



HENNEKEN
high quality equipment since 1977

Hydraulic Loader-HBS



select
TECHNOLOGIES

North American Distributor

Henneken Hydraulic Loader-HBS



Henneken Hydraulic Loader-HBS

No spill loading

The Henneken Hydraulic Loader-HBS offers a simple way to load product from a standard 400 lb. or 600 lb. industrial cart into a tumbler without losing valuable purge or liquid ingredients. The stainless steel construction, heavy duty casters, and unique compact design allows for easy maneuvering into most production areas.

The Henneken Hydraulic Loader-HBS eliminates the spill challenge by completing a full lift before the Vemag cart pivots and dumps onto the loader chute. This means liquid and solid components are delivered in the tumbler every cycle.

The loader is manufactured with standard discharge heights of 36 inches (915 mm) or 43 inches (1095 mm). Additional discharge heights are available upon request.

STANDARD FEATURES AND BENEFITS

- Self-contained 1.5 HP hydraulic power unit
- "No Spill Loading" - Dumps cart after full lift
- Compatible with 400 lb. and 600 lb. industrial standard Carts
- Standard discharge heights 36" (915 mm) or 42" (1070 mm)
- Rugged stainless steel frame with white non-marking casters
- Hygienic design for simple sanitation

AVAILABLE OPTIONS

- Alternate discharge heights
- Custom configurations are available upon request
- Dual side lift operating controls
- 480/240 - 3 phase or 120 - single phase
- Additional E-Stops and category 3 control solution

HBS Loader	Total Length	Total Width	Height (at Rest)	Dump Height	Max Lift Height (with cart)	Voltage	Electrical
Model No.	in.	in.	in.	in.	in.	3 Phase	Amps
B1-B5	67.0	40.5	70.0	36.4	93.6	480	1.5
B6-B7000	69.6	40.5	76.5	43.3	102.5	480	1.5



Tumblers

Protein activation and product massage



Injectors

Uniform brine injection of boneless and bone-in meat products



Macerators

Industrial-scale meat tenderizing



Brine Mixers

Versatile solution for liquid-based food products